

U-POL

PRODUCTS

Ready to Use

POWER CAN

CLEAR COAT

Description

Power Can Clear Coat is a 1K, ready to use clear coat in an aerosol. It is used for finishing coated surfaces in order to achieve a high gloss, UV resistant, durable finish.

Power Can Clear Coat is capable of producing a coating of a film thickness similar to that of a spray gun applied clear coat. The convenience of using a high build coating in an aerosol means that masking is kept to a minimum. Mixing paint and cleaning spray equipment are avoided as a result of using **Power Can Clear Coat** leading to savings in time and materials.

Power Can Clear Coat is isocyanate free.

Surface preparation and instructions for use

Power Can Clear Coat can be applied using the preparation procedure shown below: -

Thoroughly clean and degrease surfaces with a suitable spirit wipe or thinner such as U-POL System 20 Degreaser. Abrade solid coloured coatings wet or dry with 800-1000 abrasive, re-clean, dry and degrease. If coating solvent-based basecoats apply **Power Can Clear Coat** within a period 20-60 minutes after application of the base coat.

Application

Shake can thoroughly before use for a minimum of 2 minutes.

Apply 1-2 light even coats.

Allow 5-10 minutes flash off time between coats.

Drying time

Allow 30 minutes before handling.

Drying time is dependent upon film thickness, humidity and temperature.

Product code

PCLC/AL - 500ml aerosol