

U-POL™

SAFETY DATA SHEET 2K SYSTEM 20 CLEAR COAT

Page 1
Issued: 21/04/2004
Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 2K SYSTEM 20 CLEAR COAT

Product code: S2080

Use / description of product: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

Company name: U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: 44-(0)-1933 230300

Fax: 44-(0)-1933 230351

Emergency tel: 44-(0)-1933 230310

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: XYLENE 10-30%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- N-BUTYL ACETATE 1-10%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [Xi] R66; [-] R67

- 4-METHYLPENTAN-2-ONE 1-10%

EINECS: 203-550-1 CAS: 108-10-1

[F] R11; [Xn] R20; [Xi] R36/37; [Xi] R66

- 2-METHOXY-1-METHYLETHYL ACETATE 1-10%

EINECS: 203-603-9 CAS: 108-65-6

[-] R10; [Xi] R36

- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 1-10%

EINECS: 265-199-0 CAS: 64742-95-6

[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

[cont...]

SAFETY DATA SHEET
2K SYSTEM 20 CLEAR COAT

Other hazards: Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

Exposure hazards: Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: XYLENE

TWA (8 hr exposure limit): 220 mg/m³ STEL (15 min exposure limit): 441 mg/m³ (OES)

- N-BUTYL ACETATE

TWA (8 hr exposure limit): 724 mg/m³ STEL (15 min exposure limit): 966 mg/m³ (OES)

- 4-METHYLPENTAN-2-ONE

TWA (8 hr exposure limit): 208 mg/m³ STEL (15 min exposure limit): 416 mg/m³ (OES)

- 2-METHOXY-1-METHYLETHYL ACETATE

TWA (8 hr exposure limit): 274 mg/m³ STEL (15 min exposure limit): 822 mg/m³ (OES)

SAFETY DATA SHEET
2K SYSTEM 20 CLEAR COAT

- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Compressed airline breathing apparatus (EN139).
- Hand protection:** Nitrile gloves.
- Eye protection:** Face-shield.
- Skin protection:** Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Colourless
- Odour:** Aromatic
- Evaporation rate:** Moderate
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Insoluble
- Also soluble in:** Most organic solvents.
- Viscosity:** Viscous
- Viscosity value:** 6000cps
- Flammability limits %: lower:** 1.0
- upper:** 6.6
- Flash point°C:** 24
- Autoflammability°C:** 490
- Relative density:** 1.6
- VOC g/l:** 520

10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions.
- Conditions to avoid:** Direct sunlight. Heat. Sources of ignition. Flames.
- Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** XYLENE
- ORL MUS LD50 2119 mg/kg
- ORL RAT LD50 4300 mg/kg
- SCU RAT LD50 1700 mg/kg
- N-BUTYL ACETATE
- ORL MUS LD50 6 gm/kg
- ORL RAT LD50 10768 mg/kg
- 4-METHYLPENTAN-2-ONE
- IPR RAT LD50 400 mg/kg
- ORL MUS LD50 1900 mg/kg
- ORL RAT LD50 2080 mg/kg

SAFETY DATA SHEET
2K SYSTEM 20 CLEAR COAT

- 2-METHOXY-1-METHYLETHYL ACETATE
IPR MUS LD50 750 mg/kg
ORL RAT LD50 8532 mg/kg
- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM),
LIGHT AROM.
ORL RAT LD50 8400 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Volatile. Heavier than water.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D10 Incineration on land.
R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1263	ADR Class: 3
Packing group: III	Classification code: F1
Shipping name: PAINT RELATED MATERIAL	
Labelling: 3	Hazard ID no: 30



IMDG / IMO

UN no: 1263	Class: 3
Packing group: III	EmS: F-E,S-E
Marine pollutant: .	Labelling: 3

IATA / ICAO

UN no: 1263	Class: 3
Packing group: III	Packing instructions: 309(P&CA); 310(CAO)
Labelling: 3	

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour/spray
S36/37: Wear suitable protective clothing and gloves.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

VbF: All

Water hazard class: 1 Classification by VwVwS

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R11: Highly flammable.
R20: Harmful by inhalation.
R36/37: Irritating to eyes and respiratory system.
R36: Irritating to eyes.
R12: Extremely flammable.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.