

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product information**

Product name : ENERGY LINE ANTICORROSIVE PRIMER

Product code : L0EL0030L0.4

Company : Lechler SpA
Via Cecilio 17
22100 Como

Telephone : +39031586111

Telefax : +39031586206

In order to get more information and in case of emergencies please address to Lechler Group Security Office. (Tel. +39-031-586.301).

: Tel. +39-031-586301

Fax +39-031-586299

2. COMPOSITION/INFORMATION ON INGREDIENTS**Chemical nature** : Mono compound rust inhibitor**Hazardous components** :

Components	CAS-No.	EEC-No.	Symbol(s)	R-phrase(s)	Concentration [%]
Xylene	1330-20-7	601-022-00-9	Xn	R20/21, R38, R10	>= 12,5 - < 20
Isobutanol	78-83-1	603-108-00-1	Xi	R10, R41, R67, R37/38	>= 10 - < 12,5
Monopropylene Glycol Methyl Ether	107-98-2	603-064-00-3		R10	>= 3 - < 5
Ethyl Methyl Ketone	78-93-3	606-002-00-3	Xi, F	R11, R66, R67, R36	>= 5 - < 7
N-Butyl Acetate	123-86-4	607-025-00-1		R10, R66, R67	>= 1 - < 3
Ethoxypropylacetate	54839-24-6			R10	>= 1 - < 3
DIMETILETERE	115-10-6	603-019-00-8	F+	R12	>= 30 - < 50
GPL			F+	R12	>= 10 - < 12,5

3. HAZARDS IDENTIFICATION

Harmful



Extremely flammable

Hazardous components : Xylene1,2,4-trimethylbenzene

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

R-phrase(s) :

Extremely flammable.
Also harmful by inhalation and in contact with skin.
Irritating to skin.
Risk of serious damage to eyes.

S-phrase(s) :

Keep out of reach of children.
Do not breathe spray.
Wear suitable protective clothing and eye/face protection.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.

Exceptional labelling of special preparations :

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
Also after use, do not open with force or burn.
Do not spray on a naked flame or any other incandescent material.
Keep away from sources of ignition - No smoking.
Keep away from children.

4. FIRST AID MEASURES

- | | | |
|--------------------|---|--|
| General advice | : | When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person. |
| After Inhalation | : | Remove to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious place in recovery position and seek medical advice. |
| After Skin contact | : | Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place |
| After Eye contact | : | Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Remove contact lenses.
Seek medical advice.
Put eye-washer on working place |
| After Ingestion | : | If accidentally swallowed obtain immediate medical attention.
Keep at rest.
Do not induce vomiting. |

5. FIRE-FIGHTING MEASURES

- | | | |
|------------------------------|---|---|
| Suitable extinguishing media | : | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray. |
|------------------------------|---|---|

SAFETY DATA SHEET according to EC directive 2001/58/EC
ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

- Extinguishing media which must not be used for safety reasons : Do NOT use water jet.
- Specific hazards during fire fighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Additional advice : Refer to section 15 for specific national regulation.

7. HANDLING AND STORAGE

Handling

- Safe handling advice : Avoid exceeding of the given occupational exposure limits (see section 8).
Use only in area provided with appropriate exhaust ventilation.
Avoid contact with skin, eyes and clothing.
Smoking, eating and drinking should be prohibited in the application area.
Avoid inhalation of vapour or mist.
For personal protection see section 8.
Thoroughly mix before using
After using, store in a well-sealed container
- Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

Storage

- Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
Electrical installations / working materials must comply with the technological safety standards.
Keep away from sources of ignition - No smoking.
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value [mg/m ³]	Value [ppm]	Basis
Xylene	1330-20-7	221,00	50,00	
Isobutanol	78-83-1	152,00	50,00	
Monopropylene Glycol Methyl Ether	107-98-2	375,00	100,00	
Ethyl Methyl Ketone	78-93-3	600,00	200,00	
N-Butyl Acetate	123-86-4	713,00	150,00	
Ethoxypropylacetate	54839-24-6	597,00	100,00	
DIMETILETERE	115-10-6	1.920,00	1.000,00	

Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.
- Hand protection : For prolonged or repeated contact use protective gloves.
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin should be washed after contact.
Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact.

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.
Personnel should wear protective clothing
Workers should wear antistatic footwear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : aerosol
Flash point : < -1 °C
Solids by weight : 12 %

10. STABILITY AND REACTIVITY

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system.
Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
Inhalation of airborne droplets may cause irritation of the respiratory tract.
Note : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

Isobutanol

OBSERVATIONS ON HUMAN SUBJECTS: Exposure through inhalation causes coughing, irritation to the mucous membranes, dermatitis, headache, dizziness and drowsiness, irritation to the nose, throat and eyes, and the formation of translucent vacuoles on the surface layer of the cornea.

N-Butyl Acetate

OBSERVATIONS ON HUMAN SUBJECTS: Inhalation: 3300 ppm (16 mg/l), for short periods, cause serious irritation to the eyes and to the nose. Inhalation: 200-300 ppm (1-1.4 mg/l), for short periods, cause moderate irritation to the eyes and to the nose. Inhaling the vapours can irritate the respiratory system. The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation. Symptoms of illness at 500 ppm. Serious toxic effects at 2,000 ppm for 60 min. TCLo: 200 ppm

12. ECOLOGICAL INFORMATION

Further information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil.
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

14. TRANSPORT INFORMATION

ADR	: UN-No Class Code Packaging group Description of the goods	1950 2 F AEROSOL
IMDG	: UN-No Class EmS Packaging group Marine pollutant Description of the goods	1950 2.1 F-D, S-U AEROSOLS

15. REGULATORY INFORMATION

Hazardous components which must be listed on the label:

- Xylene
- 1,2,4-trimethylbenzene

Symbol(s) : Xn Harmful
F+ Extremely flammable

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

R-phrases(s) : R12 Extremely flammable.
 R20/21 Also harmful by inhalation and in contact with skin.
 R38 Irritating to skin.
 R41 Risk of serious damage to eyes.

S-phrases(s) : S 2 Keep out of reach of children.
 S23 Do not breathe spray.
 S36/39 Wear suitable protective clothing and eye/face protection.
 S46 If swallowed, seek medical advice immediately and show this container or label.
 S51 Use only in well-ventilated areas.

Exceptional labelling of special preparations : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C., Also after use, do not open with force or burn., Do not spray on a naked flame or any other incandescent material., Keep away from sources of ignition - No smoking., Keep away from children.

National legislation

Germany

Risk classification according to BetrSichV (Germany) : AI
 Water contaminating class (Germany) : highly water endangering

16. OTHER INFORMATION

Further information

Xylene	R20/21 R38 R10	Harmful by inhalation and in contact with skin. Irritating to skin. Flammable.
Isobutanol	R10 R41 R67 R37/38	Flammable. Risk of serious damage to eyes. Vapours may cause drowsiness and dizziness. Irritating to respiratory system and skin.
Monopropylene Glycol Methyl Ether	R10	Flammable.
Ethyl Methyl Ketone	R11 R66 R67 R36	Highly flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes.
N-Butyl Acetate	R10 R66 R67	Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
Ethoxypropylacetate	R10	Flammable.

ENERGY LINE ANTICORROSIVE PRIMER

Version

Print Date 14/12/2004

DIMETILETERE R12 Extremely flammable.

GPL R12 Extremely flammable.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version:

Revision date 00.00.0000

SDS updated to the last adjustment of EEC directive 67/548/CE, 1999/45/CE.