


FAST FILLER



Ready for use



Film thickness:
40-60 μ



Air drying at 20° C:
1-2 h.

DESCRIPTION

Coloured one component anticorrosive insulating filler, ready for use in an aerosol and available in light grey (EL070), yellow (EL072), blue (EL074), red (EL076), dark grey (EL078).

USE

Special product used in Car Refinish as insulating filler for the carrying out of small repairs (FAST REPAIRS).

CHARACTERISTICS

- Easy to use ready for use (aerosol)
- Quick drying
- Easy sanding
- Good insulating power
- Good filling power
- Ideal as undercoat for coloured finishes

SUBSTRATE PREPARATION

Old finishes

Top coats, fillers and putties must be degreased with 00695 SOLVENTE ANTISILICONE SLOW and sanded **Metal**

Apply one cross coat of EL030 ANTICORROSIVE PRIMER

For further information about the product's use in FAST REPAIRS cycles see Data Sheets Cycles N° 006 and N° 007.

APPLICATION

Spraying.

Ready for use. Shake well 2-3 minutes before use.

Spray temperature: 15-30° C

N° of coats: 1-2

Spray distance: 20-25 cm

Flash-off: 5-10 minutes at 20°C

Recommended film thickness: 40-60 μ

DRYING TIMES

Air drying at 20°C

Dust-free: 5-10 minutes
Tack-free: 20-30 minutes
Sanding after 1-2 hours

SANDING

Wet: P500 grit paper for pastel finishes and P600-800 grit paper for two-coat metallic finishes.

Dry: P320 grit paper for pastel finishes and P400 grit paper for two-coat metallic finishes.

SUGGESTED OVERCOATINGS

All the top coats of the Lechler Refinish range can be overcoated.

For further information about the product's use in FAST REPAIRS cycles see Data Sheets Cycles N° 006 and N° 007.

ATTENTION: After use turn the aerosol upside down and spray the rest out of the supplying pipe in order to avoid blockage problems during the storage time before the following use.

SHELF LIFE at 20°C: 24 months

TECHNICAL DATA SHEET N. 0500-GB
UP DATED 05/2005

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy.

THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING OF ROAD VEHICLES BY QUALIFIED PERSONNEL.