

HIGH #5

Ready to Use High Build Primer

(Available in Grey, Dark Grey, Beige & White)

Description	HIGH #5 is a 1K ready to use high build primer/filler in an aerosol. It is used for priming uneven surfaces before top coating.
	High #5 is capable of producing a coating of a film thickness similar to that of a spray gun applied primer. The convenience of using a high build primer in an aerosol means that masking is kept to a minimum. Mixing paint and cleaning spray equipment are avoided as a result of using HIGH #5 leading to savings in time and materials.
	HIGH #5 is chromate free and easy to sand.
Surface preparation and instructions for use	 HIGH #5 can be applied to the following surfaces:- Fully cured paint. Polyester bodyfillers and G.R.P. Suitably prepared steel panels.
	Thoroughly clean and degrease surfaces with a suitable spirit wipe or thinner. Abrade wet or dry with 280-320 abrasive, re-clean, dry and degrease.
Application	Shake can thoroughly before use for a minimum of 2 minutes.
	Apply 1-2 light even coats.
	Allow 5-10 minutes flash off time between coats.
Drying time	Allow 10-20 minutes before overcoating.
	Drying time is dependent upon film thickness, humidity and temperature.
Over-painting	HIGH #5 should be flatted wet with 600-800 or dry with 400-600 abrasive.
	HIGH #5 may be over-painted with most paint systems.
Product code	HIGH/AL - Beige - 450ml aerosol HIGHG/AL - Grey - 450ml aerosol HIGHDG/AL - White - 450ml aerosol HIGHW/AL - White - 450ml aerosol

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 OEY, UK T: +44 (0)20 8492 5900; F:+44(0)20 8492 5999; E:SALES@U-POL.COM; W: WWW.U-POL.COM