

**PRODUCT NAME : NON SLIP 116 FLOOR PAINT****TECHNICAL DATA:**

Standard Shades : Available in all British Standard & RAL colours

DRY FILM APPEARANCE	Smooth & Glossy
SPREADING RATE	10 to 15 sq/ mtrs per litre subject to porosity
TOUCH DRY @ 20'C	2 to 3 hours
HARD DRY @ 20'C	5 - 6 days
VOLITILE ORGANIC COMPUNDS (VOC)	580 grams per litre
APPLICATION METHODS	Roller, Brush or Spray
SUBSTRATES	Suitable clean dry surfaces
THINNERS & TOOL CLEANING	00 825 Universal Thinner
FLASH POINT	Above 2 hours @ 20'C
PACK SIZES	1Ltrs, 5Ltrs

**PRODUCT BENEFITS:**

- |                          |                                   |
|--------------------------|-----------------------------------|
| * Touch surface finish   | * Easy to apply                   |
| * Excellent gloss & flow | * Fast roller / spray application |
| * Attractive colours     | * Good weather resistance         |
| * Non slip additive      |                                   |

**Description & recommended uses:** This product is a best quality floor paint synthetic based. It is available in 100's of colours for you to choose from, non slip version also available.

**How to apply:**

1. Sweep up loose debris
2. Ensure the floor is free from grease & oil
3. Where necessary paint around machinery, pillars & fixtures etc.
4. Thin the first coat with 10% thinners
5. Leave the first coat to dry overnight
6. Apply the second coat full strength
7. Leave to dry overnight

**Health & Safety :** See separate Health & Safety Datasheet.

**Paints4u.com Ltd follows a process of continuous improvement, also the application method & substrate are beyond our control. Therefore this datasheet is issued for general guidance only. It is based on tests & believed to be correct at time of going to print.**

**For further information on any of our products please don't hesitate to contact us:**  
[www.paints4u.com](http://www.paints4u.com)      [sales@paints4u.com](mailto:sales@paints4u.com)      01724 854916