



EL010 – PLASTIC PRIMER



Ready for use



Air drying at 20° C:
20-30 min.

DESCRIPTION

Universal one component primer suitable for plastic materials, ready for use in an aerosol.

USE

Special product used in Car Refinish for small repairs for all types of plastics used on cars.

CHARACTERISTICS

- Easy to use ready for use (aerosol)
- Excellent adhesion directly to plastic materials
- Quick drying
- Safe use
- Slightly silver coloured for an easier application

SUBSTRATE PREPARATION

Degrease carefully with 00660 QUICK CLEANER.

For further information about the product's use in FAST REPAIRS cycles see Data Sheet Cycle N° 007.

APPLICATION

Spraying.

Ready for use. Shake well 2-3 minutes before use.

Spray temperature: 15-30° C

N° of coats: 1 cross coat

Spray distance: 20-25 cm

Recommended film thickness: 5-10 µ

DRYING TIMES

Air drying at 20°C

20-30 min.

SUGGESTED OVERCOATINGS

Fillers and top coats of the Lechler range can be overcoated without sanding after flash-off.

For further information about the product's use in FAST REPAIRS cycles see Data Sheet Cycle N° 007



NOTE

ATTENTION: the product is not suitable for the painting of polyethylene substrates (PE). Polyethylene is used for some tanks and motorcycles' details.

After use turn the aerosol upside down and spray the rest out of the supplying pipe in order to avoid blockage problems during the storage time before the following use.

SHELF LIFE AT 20°C: 24 months

DATA SHEET N. 0498-GB
UP DATED 09/2003

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy.

THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING OF ROAD VEHICLES BY QUALIFIED PERSONNEL.