

U-POL

PRODUCTS

Ready to Use

POWER CAN

RED OXIDE PRIMER

Description

Power Can Red Oxide Primer is a 1K ready to use high build primer/filler in an aerosol. It is used for priming uneven surfaces before top coating.

Power Can Red Oxide Primer is capable of producing a coating of a film thickness similar to that of a spray gun applied primer. The convenience of using a high build primer in an aerosol means that masking is kept to a minimum. Mixing paint and cleaning spray equipment are avoided as a result of using **Power Can Red Oxide Primer** leading to savings in time and materials.

Power Can Red Oxide Primer is chromate free and easy to sand.

Surface preparation and instructions for use

Power Can Red Oxide Primer can be applied to the following surfaces:-

- Fully cured paint.
- Polyester bodyfillers and G.R.P.

Thoroughly clean and degrease surfaces with a suitable spirit wipe or thinner. Abrade wet or dry with 280-320 abrasive, re-clean, dry and degrease with a suitable degreaser or thinner such as U-POL System 20 Degreaser.

Application

Shake can thoroughly before use for a minimum of 2 minutes.

Apply 1-2 light even coats.

Allow 5-10 minutes flash off time between coats.

Drying time

Allow 10-20 minutes before overcoating.

Drying time is dependent upon film thickness, humidity and temperature.

Over-painting

Power Can Red Oxide Primer should be flatted wet with 600-800 or dry with 400-600 abrasive.

Power Can Red Oxide Primer may be over-painted with most paint systems.

Product code

PCOR/AL - 500ml aerosol