

PRODUCT NAME : VINYL TILE FLOOR PAINT**TECHNICAL DATA:**

Standard Shades : Venetian Red, Mid Grey, Brunswick Green, Light Green, Blue, Light Grey, Cream, Black & Clear. Other colours to order

DRY FILM APPEARANCE	Satin Smooth
SPREADING RATE	10 to 15 sq/ mtrs per litre subject to porosity
TOUCH DRY @ 20'C	1 Hour
FOOT TRAFFIC @ 20'C	overnight
FULLY DRY	5 Days
AVERAGE WET FILM THICKNESS	100 microns
AVERAGE DRY FILM THICKNESS	52 microns
SOLIDS BY VOLUME	52% (+/- 2%)
VOLITILE ORGANIC COMPUNDS (VOC)	570 grams per litre
APPLICATION METHODS	Roller, Brush or Spray
SUBSTRATES	Suitable clean dry surfaces
THINNERS & TOOL CLEANING	White Spirit
FLASH POINT	Above 32'C
PACK SIZES	5Ltrs, 20Ltrs
SHELF LIFE	12 months
MIN APPLICATION TEMPERATURE	7'C

PRODUCT BENEFITS:

- * Touch surface finish
- * Excellent Adhesion
- * Attractive colours
- * Easy to apply
- * Fast roller application
- * Eliminates dust permanently

Description & Recommended Uses :

This product is a formulated specifically for vinyl floor coverings. Formulated on reinforced resins to provide good adhesion & a tough & durable finish for factories, warehouses, offices, store rooms, kitchens, showrooms, workshops, schools, conservatories etc.

How to apply:

1. Sweep up loose debris
2. Ensure the floor is free from treatments such as wax, polish, grease & oil
3. To ensure good adhesion lightly abrade the surface
4. Where necessary paint around machinery, pillars & fixtures etc.
5. Thin the first coat with 10% thinners
6. Leave the first coat to dry overnight
7. Apply the second coat full strength
8. Leave to dry overnight

Helpful Hints: Unpainted floors will give a longer dust free life if treated with 2 coats. New floors should be at least 4 weeks old before painting, with a moisture content of less than 7%. Floors that are treated with a chemical hardener may not be suitable for painting if you are unsure test a small area prior to painting. It is always better to apply 2 thin coats rather than one thick coat.

Health & Safety : See separate Health & Safety Datasheet.

Paints4u.com Ltd follows a process of continuous improvement, also the application method & substrate are beyond our control. Therefore this datasheet is issued for general guidance only. It is based on tests & believed to be correct at time of going to print.

For further information on any of our products please don't hesitate to contact us:

www.paints4u.com sales@paints4u.com 01724 854916

