

30ml Paint & Lacquer Kit Application Guide

This kit can be used to remove small but deep scratches or stone chips where the primer or metal work is exposed.

Our kit comes complete with 3 double ended application spears.

These are tightly wound cotton buds that have a very fine point on each end (0.2mm). See the picture below to compare a typical lid touch-up brush against our application spears.

LACQUER	
BASE COAT	
PRIMER	
STEEL	

This Kit Contains:

- 30ml Custom Colour Base Coat Paint
- 30ml Clear Lacquer
- 3 double ended disposable application spears

Step 1

Remove any flaking paint or dirt from the damaged area and thoroughly clean the area using an application spear.

Step 2

Shake the base coat paint bottle, ensuring that the paint is evenly mixed.

Using the application spear, apply a thin layer of base coat paint.

Repeat after 30 minutes if needed.

Please ensure you leave enough depth for the lacquer.

Please leave 1-2 hours for the base coat to harden before applying the lacquer.

Step 3

When the base coat has dried, apply a thin layer of lacquer using an application spear. Leaving around 30 minutes between layers, repeat until the lacquer is flush with the surface of the existing paintwork.

Please leave at least 24 hours for the lacquer to harden before polishing.

Step 4

you can also purchase the optional repair flatting kit to level out the lacquer. See additional items listed on our website for more information.

PLEASE NOTE: The results from using the 30ml Paint & Lacquer Kit will depend entirely on the care taken by the user, please apply slowly and carefully taking as much time as needed.