


EL080 – EASY SOLVENT



Ready for use



Air drying at 20° C:
1-5 min.

DESCRIPTION

Solvent for fade out, ready for use in aerosol.

USE

Special product used in Car Refinish to fade out top coats and clearcoat.

CHARACTERISTICS

- Easy to use because ready for use (Aerosol)
- To apply directly after fading
- Quick flash-off
- High solvent power uniforming fading

SUBSTRATE PREPARATION

Application of BSB or HYDROFAN basecoat + ACRIFAN/MACROFAN clearcoat or ISOAKRYL or MACROFAN TOP COAT top coat. Allow the solvent to flash off completely (20-30 minutes at 20°C).

APPLICATION

Spraying.

Ready for use. Shake well 1-2 minutes before use.

Spray temperature: 15-30° C

N° of coats: 1 (on the uniform shade)

Spray distance: 20-25 cm

DRYING TIMES

Air drying at 20°C

1-5 minutes

Polishable: after top coat's through-drying

NOTES

Do not apply directly to the mat basecoat (BSB or HYDROFAN), but to the clearcoat (ACRIFAN or MACROFAN) and to the top coats (ISOAKRYL or MACROFAN TOP COAT).



ATTENTION: After use turn the aerosol upside down and spray the rest out of the supplying pipe in order to avoid blockage problems during the storage time before the following use.

SHELF LIFE AT 20°C: 24 months

DATA SHEET N. 0505-GB
UP DATED 09/2003

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy.

THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING OF ROAD VEHICLES BY QUALIFIED PERSONNEL.



LECHLER S.p.A. 22100 Como Italy - Via Cecilio,17 Tel. +39/031/586.111